

PUBLISHED: 10-JUL-2019
2020.0 DEFENDER (LE), 303-14B

ELECTRONIC ENGINE CONTROLS – INGENIUM I6 3.0L PETROL

POST CATALYST HEATED OXYGEN SENSOR (G2344543)

mcx30.com

SPECIAL TOOL(S)



E213446

JLR-303-1666

Remover/Installer, NOx/Oxygen Sensor

REMOVAL

**WARNING:**

Observe due care when working near a hot exhaust system.

**NOTE:**

- This procedure contains illustrations showing certain components removed to provide extra clarity.
- This procedure contains some variation in the illustrations depending on the vehicle specification, but the essential information is always correct.

1.

Raise and support the vehicle on a suitable 2 post lift.


Refer to: [Jacking and Lifting](#) (100-02 Jacking and Lifting, Description and Operation).

2.

Remove the engine undershield.


Refer to: [Engine Undershield](#) (501-02 Front End Body Panels, Removal and Installation).

3.




- Remove the 20 bolts.
- Remove the transmission undershield cover.

4.




- Remove the 8 bolts.
- Remove the transmission undershield.

5.




Release and reposition the noise, vibration and harshness material as illustrated.

6.



- Disconnect the electrical connector.
- Release the wiring harness from the clip.



Use the special tool to remove the post catalyst heated oxygen sensor.

Special Tool(s): [JLR-303-1666](#)

INSTALLATION

1.

⚠ CAUTION:

- If accidentally dropped or knocked install a new sensor.
- Make sure that the sensor tip is clean and free of foreign material.

Use the special tool to install and tighten the post catalyst heated oxygen sensor.

Special Tool(s): [JLR-303-1666](#)

Torque: **48Nm**

2.

- Connect the electrical connector.
- Install the wiring harness into the clip.

3.

Install the noise, vibration and harshness material into the correct location.

4.

- Install the transmission undershield.
- Install and tighten the 8 bolts.

Torque: **60Nm**

5.

- Install the transmission undershield cover.
- Install and tighten the 20 bolts.

Torque: **10Nm**

6.

Install the engine undershield.

Refer to: [Engine Undershield](#) (501-02 Front End Body Panels, Removal and Installation).