

PUBLISHED: 20-JUN-2019
2020.0 DEFENDER (LE), 413-09

WARNING DEVICES

SIDE OBSTACLE DETECTION CONTROL MODULE

[G2410748]

mcx30.com

GENERAL EQUIPMENT

EQUIPMENT NAME
Jaguar Land Rover approved diagnostic equipment

REMOVAL

 NOTES:

- This procedure contains some variation in the illustrations depending on the vehicle specification, but the essential information is always correct.
- This procedure contains illustrations showing certain components removed to provide extra clarity.
- This procedure contains illustrations for left side components, right side components are similar.

1. Disconnect the startup battery ground cable.
Refer to: [Startup Battery Disconnect and Connect](#) (414-00 Battery and Charging System - General Information, General Procedures).

2. Raise and support the vehicle on a suitable 2 post lift.
Refer to: [Jacking and Lifting](#) (100-02 Jacking and Lifting, Description and Operation).

3. Remove the rear bumper.
Refer to: [Rear Bumper](#) (501-19 Bumpers, Removal and Installation).

E250077

- ## INSTALLATION

NOTE:

- Install the side obstacle detection control module.
- Connect the electrical connector.

Refer to: [Rear Bumper](#) (501-19 Bumpers, Removal and Installation).

Refer to: [Startup Battery Disconnect and Connect](#) (414-00 Battery and Charging System - General Information, General Procedures).

General Equipment: Jaguar Land Rover approved diagnostic equipment