

2022 CHEVROLET CORVETTE SERVICE MANUAL

- **SEARCH**

1. **Power and Signal Distribution**
2. **Wire and Connector Repair**
3. **Repair Instructions**
- 4.

0.64 YESC Kaizen Series Connectors

Special Tools

- J-38125-215A

For equivalent regional tools, refer to Special Tools.

Connector Removal Procedure

1. Click here for full size
2. Slide the Connector Position Assurance (CPA) away from the mating component until it is fully released.
3. Once the CPA is released press the connector lock to release the connector and pull it away from the mating component.

Terminal Removal Procedure

1. Click here for full size
2. Disengage the TPA to the released position by using a small screwdriver to gently pry it away from the connector body, it may be necessary to alternate side to side until fully released shown above.
3. Click here for full size
4. Insert removal tool J-38125-215A into the access hole of the terminal being removed until the locking tab is released, then gently pull on the wire to remove the terminal from the connector.

Terminal Installation Procedure

1. Verify the terminal is oriented to the connector properly.
2. Once terminal is properly aligned, fully insert the terminal straight into the cavity until an audible click is heard or felt when the terminal is fully inserted. Gently pull on wire to verify it is fully seated.
3. Push the TPA towards the connector body until it is fully seated to lock and secure the terminal. This should require very little effort, if excessive effort is needed, reinspect terminal is position correctly, fully seated and the terminal lock is fully engaged.