

2022 CHEVROLET CORVETTE SERVICE MANUAL

- **SEARCH**

1. **Roof**
2. **Folding Top**
3. **Repair Instructions**
- 4.

Folding Top Motor Replacement

Removal Procedure

1. Click here for full size
2. Folding Top Motor Cover >> Remove Folding Top Motor Cover Replacement
3. Click here for full size
4. Disconnect the electrical connector.
5. Folding Top Motor Bracket Bolt (1) >> Remove [2x]
6. Remove the folding top motor and bracket (2).
7. Click here for full size
8. Folding Top Motor Bolt (1) >> Remove [4x]
9. Remove the folding top motor (2) from the bracket.

Installation Procedure

1. Click here for full size
2. Install the folding top motor (2) to the bracket.
3. If NEW threaded components are being installed, loosen the adhesive using a metal pick or similar tool before proceeding. If threaded components are reused, prepare the threaded components using the following steps:
4.
 1. Remove any loose cured adhesive from the external threads of the components using a lint free cloth.
 2. Thread the cleaned components into the internal mating threads and remove to loosen trapped cured adhesive.
 3. Apply thread locking adhesive to the external threads of the components. Adhesives, Fluids, Lubricants, and Sealers
 4. Ensure there are no gaps in the thread locking adhesive once applied to the component.
5. Caution:
Refer to Fastener Caution.
6. Folding Top Motor Bolt (1) >> Install and tighten [4x]9>N-m (80 lb in)
7. Click here for full size
8. Install the folding top motor and bracket (2).
9. If NEW threaded components are being installed, loosen the adhesive using a metal pick or similar tool before proceeding. If threaded components are reused, prepare the threaded components using the following steps:
10.
 1. Remove any loose cured adhesive from the external threads of the components using a lint free cloth.
 2. Thread the cleaned components into the internal mating threads and remove to loosen trapped cured adhesive.

3. Apply thread locking adhesive to the external threads of the components. Adhesives, Fluids, Lubricants, and Sealers
4. Ensure there are no gaps in the thread locking adhesive once applied to the component.
11. Folding Top Motor Bracket Bolt (1) >> Install and tighten [2x]15N-m (11 lb ft)
12. [Click here for full size](#)
13. Folding Top Motor Cover >> Install Folding Top Motor Cover Replacement
14. Perform the rear window normalization. Rear Window Normalization

mcx30.com