

2022 CHEVROLET CORVETTE SERVICE MANUAL

- **SEARCH**

1. **Roof**
2. **Folding Top**
3. **Repair Instructions**
- 4.

Folding Top Stowage Compartment Lid Hinge Replacement

Removal Procedure

Warning:

When the folding top or folding top stowage compartment lid is opening or closing, personal injury may occur by the parts in motion. Ensure all individuals involved maintain a safe distance from these parts while operating to avoid any personal injury or vehicle damage

Warning:

Components under the folding top stowage compartment lid, close to the engine, can get hot from running the engine. To help avoid the risk of burning unprotected skin, never touch these components until they have cooled, and always use a glove or towel to avoid direct skin contact.

Caution:

Follow these guidelines when operating the folding top or damage can occur:

- Remove all items from the roof, trunk lid, or folding top stowage compartment lid before operating
- Remove all objects that may contact the folding top when it is operated.
- Do not leave the vehicle with the folding top open.
- Do not exceed 50 km/h (31 mph) until the folding top has completely closed or opened.
- Do not open or close the folding top while driving in high wind conditions.
- Do not operate the folding top multiple times in a short period of time without starting the engine to avoid draining the vehicle battery.
- Only store the vehicle with the folding top fully closed.

1. Open the rear compartment lid.
2. Mark the position of the hinges with a grease pencil.
3. [Click here for full size](#)
4. Folding Top Stowage Compartment Lid Hinge Bolt (1) >> Remove [4x]
5. Folding Top Stowage Compartment Lid Hinge (2) >> Remove

Installation Procedure

1. [Click here for full size](#)
2. **Warning:**

Refer to Eye Protection Warning.

3. **Note:**

If replacing the hinge, the new hinge will need to be drilled using diameter showing below prior to installation. Use dimpled locations marked on the hinge.

4. Carefully drill the forward most dimple (1) with a 11 mm drill bit.
5. Carefully drill the rearward most dimple (2) with a 12 mm drill bit.
6. [Click here for full size](#)

7. Folding Top Stowage Compartment Lid Hinge (2) >> Install
8. Caution:
Refer to Fastener Caution.
9. Folding Top Stowage Compartment Lid Hinge Bolt @ Rear Compartment Lid (1) >> Install and tighten [4x]22N-m (16 lb ft)
10. [Click here for full size](#)
11. Folding Top Stowage Compartment Lid Hinge Bolt @ Folding Top Stowage Compartment Lid (1) >> Install and tighten [4x]25N-m (18 lb ft)
12. Adjust if necessary. Folding Top Stowage Compartment Lid Adjustment

mcx30.com