

2010 STEERING

Power Steering - Equinox & Terrain

SPECIFICATIONS

FASTENER TIGHTENING SPECIFICATIONS

Application	Specification	
	Metric	English
Power Steering Assist Motor Bolt	8 N.m	71 lb in
Power Steering Fluid Cooling Pipe Bolt	9 N.m	80 lb in
Power Steering Fluid Cooling Pipe Fitting	34 N.m	25 lb ft
Power Steering Fluid Cooling Pipe Nut	9 N.m	80 lb in
Power Steering Fluid Reservoir Bolt	9 N.m	80 lb in
Power Steering Fluid Reservoir Nut	9 N.m	80 lb in
Power Steering Gear Inlet Hose Fitting	34 N.m	25 lb ft
Power Steering Pump Bolt	23 N.m	17 lb ft
Steering Gear Bolt	110 N.m	81 lb ft
Steering Gear Heat Shield Bolt	9 N.m	80 lb in
Steering Gear Pipe Fitting	15 N.m	11 lb ft
Steering Linkage Inner Tie Rod	105 N.m	77 lb ft
Steering Linkage Outer Tie Rod Nut	60 N.m	44 lb ft

POWER STEERING PUMP SPECIFICATIONS

Vehicle	Engine Code	Engine Size	High Flow		Pressure Relief	
			LPM	GPM	kPa	PSI
Chevrolet Equinox / GMC Terrain	LF1	3.0 L	9.5/11.5	2.51/3.04	12000/12800	1740/1856

ADHESIVES, FLUIDS, LUBRICANTS, AND SEALERS

Application	Type of Material	GM Part Number	
		United States	Canada
Power Steering Fluid	DEXRON® VI ATF	88861003	88861004

SCHEMATIC AND ROUTING DIAGRAMS

POWER STEERING SCHEMATICS