

2018 BRAKES

Antilock Brake System - Equinox & Terrain

SPECIFICATIONS

FASTENER SPECIFICATIONS

Reusable Threaded Fastener Tightening Specifications

NOTE: <i>All fasteners listed in this table can be reused after removal.</i>	
Application	Specification
	Metric (English)
Brake Pipe Fitting - Left Front, Left Rear, Right Front, Right Rear	18 N.m (13 lb ft)
Brake Pressure Modulator Valve Bolt	9 N.m (80 lb in)
Brake Pressure Modulator Valve Bracket Bolt	9 N.m (80 lb in)
Brake Pressure Modulator Valve Bracket Nut	9 N.m (80 lb in)
Brake Pressure Modulator Valve Primary Pipe Fitting	25 N.m (18 lb ft)
Brake Pressure Modulator Valve Secondary Pipe Fitting	25 N.m (18 lb ft)
Electronic Brake Control Module Bolt	5.1 N.m (45 lb in)
Front Wheel Speed Sensor Bolt	6 N.m (53 lb in)
Front Brake Hose Bolt	9 N.m (80 lb in)
Rear Wheel Speed Sensor Bolt	6 N.m (53 lb in)

SCHEMATIC WIRING DIAGRAMS

ANTILOCK BRAKE SYSTEM WIRING SCHEMATICS

Power, Ground, Serial Data, Traction Control and References