

2018 ENGINE
Exhaust - Equinox & Terrain

SPECIFICATIONS

FASTENER SPECIFICATIONS

Single Use Non-Threaded Fasteners/Components

NOTE: <i>All fasteners/components listed in this table MUST BE DISCARDED and replaced with NEW after removal.</i>	
Application	
Catalytic Converter Gasket	
Exhaust Gasket	
Exhaust Manifold Gasket	

Single Use Threaded Fastener/Component Tightening Specifications

NOTE: <i>All fasteners/components listed in this table MUST BE DISCARDED and replaced with NEW after removal.</i>	
Application	Specification
	Metric (English)
Catalytic Converter Clamp (LH7)	6 N.m (53 lb in)
Exhaust Manifold Bolt (LTG)	20 N.m (15 lb ft)
Exhaust Manifold Bolt (LH7)	
First Pass:	20 N.m (15 lb ft)
Second Pass:	20 N.m (15 lb ft)
Final Pass:	20 N.m (15 lb ft)

Reusable Threaded Fastener Tightening Specifications

NOTE: <i>All fasteners listed in this table can be reused after removal.</i>	
Application	Specification
	Metric (English)
Catalytic Converter Brace Bracket Bolt (LTG, LYX)	22 N.m (16 lb ft)
Catalytic Converter Brace Bracket Nut (LYX)	22 N.m (16 lb ft)
Catalytic Converter Brace Bracket Nut (LH7)	22 N.m (16 lb ft)
Catalytic Converter Brace Bracket Nut @ Transmission Housing Stud (LYX)	58 N.m (43 lb ft)
Catalytic Converter Brace Nut {LH7}	22 N.m (16 lb ft)
Catalytic Converter Clamp (LH7)	25 N.m (18 lb ft)
Catalytic Converter Clamp Bolt (LYX)	15 N.m (11 lb ft)
Catalytic Converter Heat Shield Bolt (LTG)	10 N.m (89 lb in)
Catalytic Converter Heat Shield Bolt (LH7)	10 N.m (89 lb in)
Catalytic Converter Nut (LTG, LYX)	22 N.m (16 lb ft)
Catalytic Converter Nut @Turbocharger (LTG)	50 N.m (37 lb ft)
Catalytic Converter Stud (LH7)	9 N.m (80 lb in)
Exhaust Front Pipe Bracket Bolt (LTG)	22 N.m (16 lb ft)
Exhaust Front Pipe Hanger Bracket Bolt (LTG)	22 N.m (16 lb ft)