

2018 STEERING

Power Steering - Equinox & Terrain

SPECIFICATIONS

FASTENER SPECIFICATIONS

Single Use Non-Threaded Fasteners/Components

NOTE: <i>All fasteners/components listed in this table MUST BE DISCARDED and replaced with NEW after removal.</i>	
Application	
Power Steering Assist Motor Seal	
Steering Gear Boot Inner Clamp	

Single Use Threaded Fastener/Component Tightening Specifications

NOTE: <i>All fasteners/components listed in this table MUST BE DISCARDED and replaced with NEW after removal.</i>	
Application	Specification
	Metric (English)
Power Steering Assist Motor Bolt	21 N.m (15 lb ft)

Reusable Threaded Fastener Tightening Specifications

NOTE: <i>All fasteners listed in this table can be reused after removal.</i>	
Application	Specification
	Metric (English)
Steering Gear Bolt	
• First Pass:	100 N.m (74 lb ft)
• Final Pass:	45 - 60 degrees
Steering Linkage Inner Tie Rod	105 N.m (77 lb ft)
Steering Linkage Outer Tie Rod Nut	
• First Pass:	35 N.m (26 lb ft)
• Final Pass:	80 - 90 degrees

SCHEMATIC WIRING DIAGRAMS

POWER STEERING WIRING SCHEMATICS

Power Steering