

2018 SUSPENSION**CHEVROLET WHEEL ALIGNMENT SPECIFICATIONS - EQUINOX****WHEEL ALIGNMENT SPECIFICATIONS****EQUINOX AWD MODELS****EQUINOX AWD Models**

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($\hat{A}^\circ$)	3.7	4.5	5.3
Right Front Caster ($\hat{A}^\circ$)	3.7	4.5	5.3
Left Front Camber ($\hat{A}^\circ$)	-1.05	-0.35	0.35
Right Front Camber ($\hat{A}^\circ$)	-1.05	-0.35	0.35
Front Toe ($\hat{A}^\circ$)	0	0.2	0.4
Left SAI ($\hat{A}^\circ$)	0	0	0
Right SAI ($\hat{A}^\circ$)	0	0	0
Left Rear Camber ($\hat{A}^\circ$)	-1.3	-0.5	0.3
Right Rear Camber ($\hat{A}^\circ$)	-1.3	-0.5	0.3
Rear Toe ($\hat{A}^\circ$)	-0.1	0.1	0.3
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Left Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Outward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Outward ($\hat{A}^\circ$)	0	-	-

EQUINOX FWD MODELS**EQUINOX FWD Models**

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($\hat{A}^\circ$)	3.7	4.5	5.3
Right Front Caster ($\hat{A}^\circ$)	3.7	4.5	5.3
Left Front Camber ($\hat{A}^\circ$)	-1.2	-0.5	0.2
Right Front Camber ($\hat{A}^\circ$)	-1.2	-0.5	0.2
Front Toe ($\hat{A}^\circ$)	0	0.2	0.4
Left SAI ($\hat{A}^\circ$)	0	0	0
Right SAI ($\hat{A}^\circ$)	0	0	0
Left Rear Camber ($\hat{A}^\circ$)	-1.3	-0.5	0.3
Right Rear Camber ($\hat{A}^\circ$)	-1.3	-0.5	0.3
Rear Toe ($\hat{A}^\circ$)	-0.1	0.1	0.3
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Left Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Outward ($\hat{A}^\circ$)	0	0	0

Measurement	Minimum	Preferred	Maximum
Right Max Turn, Outward (Â°)	0	-	-

mcx30.com