

2018 SUSPENSION**CHEVROLET WHEEL ALIGNMENT SPECIFICATIONS****WHEEL ALIGNMENT SPECIFICATIONS****BOLT EV****BOLT EV 205/55 R16**

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($^{\circ}$)	4.75	5.5	6.25
Right Front Caster ($^{\circ}$)	4.75	5.5	6.25
Left Front Camber ($^{\circ}$)	-1.3	-0.55	0.2
Right Front Camber ($^{\circ}$)	-1.3	-0.55	0.2
Front Toe ($^{\circ}$)	-0.18	0.02	0.22
Left SAI ($^{\circ}$)	0	0	0
Right SAI ($^{\circ}$)	0	0	0
Left Rear Camber ($^{\circ}$)	-1.9	-1.4	-0.9
Right Rear Camber ($^{\circ}$)	-1.9	-1.4	-0.9
Rear Toe ($^{\circ}$)	-0.15	0.2	0.55
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($^{\circ}$)	0	0	0
Right Toe Out, Inward ($^{\circ}$)	0	0	0
Left Toe Out, Outward ($^{\circ}$)	0	0	0
Right Toe Out, Outward ($^{\circ}$)	0	0	0
Left Max Turn, Inward ($^{\circ}$)	0	0	0
Right Max Turn, Inward ($^{\circ}$)	0	0	0
Left Max Turn, Outward ($^{\circ}$)	0	0	0
Right Max Turn, Outward ($^{\circ}$)	0	-	-

BOLT EV 215/50 R17

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($^{\circ}$)	4.75	5.5	6.25
Right Front Caster ($^{\circ}$)	4.75	5.5	6.25
Left Front Camber ($^{\circ}$)	-1.3	-0.55	0.2
Right Front Camber ($^{\circ}$)	-1.3	-0.55	0.2
Front Toe ($^{\circ}$)	-0.18	0.02	0.22
Left SAI ($^{\circ}$)	0	0	0
Right SAI ($^{\circ}$)	0	0	0
Left Rear Camber ($^{\circ}$)	-1.9	-1.4	-0.9
Right Rear Camber ($^{\circ}$)	-1.9	-1.4	-0.9
Rear Toe ($^{\circ}$)	-0.15	0.2	0.55
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($^{\circ}$)	0	0	0
Right Toe Out, Inward ($^{\circ}$)	0	0	0
Left Toe Out, Outward ($^{\circ}$)	0	0	0
Right Toe Out, Outward ($^{\circ}$)	0	0	0
Left Max Turn, Inward ($^{\circ}$)	0	0	0
Right Max Turn, Inward ($^{\circ}$)	0	0	0
Left Max Turn, Outward ($^{\circ}$)	0	0	0
Right Max Turn, Outward ($^{\circ}$)	0	-	-