



1. To install, reverse the removal procedure.

## Front Stabilizer Bar Link

### Removal

**NOTICE:** Suspension fasteners are critical parts that affect the performance of vital components and systems. Failure of these fasteners may result in major service expense. Use the same or equivalent parts if replacement is necessary. Do not use a replacement part of lesser quality or substitute design. Tighten fasteners as specified.



**NOTE:** Removal steps in this procedure may contain installation details.

1. Remove the wheel and tire.  
Refer to: Wheel and Tire (204-04A Wheels and Tires, Removal and Installation).
2. **NOTICE:** Do not use power tools to remove or install the stabilizer bar link nuts. Damage to the stabilizer bar link ball joints and boots may occur.

**NOTE:** The stabilizer bar links are designed with low friction ball joints that have a low breakaway torque.

**NOTE:** Use the TORX PLUS<sup>®</sup> holding feature to prevent the ball stud from turning while removing or installing the stabilizer bar link nut. Torx<sup>®</sup> and TORX PLUS<sup>®</sup> is a reg. tm of Acument Intellectual Properties, LLC.

1. Remove and discard the front stabilizer bar link lower nut.  
Torque: 129 lb.ft (175 Nm)
2. Position aside the front stabilizer bar link.




3. **NOTICE:** Do not use power tools to remove or install the stabilizer bar link nuts. Damage to the stabilizer bar link ball joints and boots may occur.

**NOTE:** The stabilizer bar links are designed with low friction ball joints that have a low breakaway torque.

**NOTE:** Use the TORX PLUS<sup>®</sup> holding feature to prevent the ball stud from turning while removing or installing the stabilizer bar link nut. Torx<sup>®</sup> and TORX PLUS<sup>®</sup> is a reg. tm of Acument Intellectual Properties, LLC.

1. Remove and discard the front stabilizer bar link upper nut.  
Torque: 129 lb.ft (175 Nm)
2. Remove the front stabilizer bar link.



**Installation**

1. To install, reverse the removal procedure.

mcx30.com