

*SECTION 501-14: Handles, Locks, Latches and Entry Systems*  
**SPECIFICATIONS**

*2014 F-150 Workshop Manual*  
 Procedure revision date: 10/25/2013

**Material**

| Item                                                                                         | Specification | Fill Capacity |
|----------------------------------------------------------------------------------------------|---------------|---------------|
| Multi-Purpose Grease XG-4 and/or XL-5                                                        | ESB-M1C93-B   | —             |
| Penetrating and Lock Lubricant (US); Penetrating Fluid (Canada) XL-1 (US); CXC-51-A (Canada) | —             | —             |

**Torque Specifications**

| Description                              | Nm | lb-ft | lb-in |
|------------------------------------------|----|-------|-------|
| Door latch bolts                         | 12 | —     | 106   |
| Door latch striker bolts                 | 25 | 18    | —     |
| Exterior door handle bolt                | 7  | —     | 62    |
| Exterior door handle nuts                | 7  | —     | 62    |
| Hood latch bolts                         | 35 | 26    | —     |
| Pickup bedside step latch nuts           | 9  | —     | 80    |
| Primary hood latch release handle bolt   | 9  | —     | 80    |
| Secondary hood latch release handle bolt | 8  | —     | 71    |
| Tailgate access panel bolts              | 5  | —     | 44    |
| Tailgate latch bolts                     | 25 | 18    | —     |
| Tailgate latch striker                   | 40 | 30    | —     |
| Tailgate release handle nuts             | 9  | —     | 80    |

mcx30.com