

Disconnect and inspect all the BCM connectors.

Repair:

corrosion (install new connectors or terminals - clean module pins)

damaged or bent pins - install new terminals pins

pushed-out pins - install new pins as necessary

Reconnect the BCM connectors and make sure they seat and latch correctly.

Operate the system and determine if the concern is still present.

Is the concern still present?

Yes	CHECK OASIS for any applicable Technical Service Bulletins (TSBs). If a TSB exists for this concern, DISCONTINUE this test and FOLLOW TSB instructions. If no Technical Service Bulletins (TSBs) address this concern,
No	The system is operating correctly at this time. The concern may have been caused by module connections. ADDRESS the root cause of any connector or pin issues.

DIAGNOSIS AND TESTING > LOCKS, LATCHES AND ENTRY SYSTEMS > PINPOINT TESTS > PINPOINT TEST J : A SINGLE OR MORE THAN ONE DOOR LOCK IS INOPERATIVE

Refer to Remote Keyless Entry and Alarm for schematic and connector information.

Normal Operations and Fault Conditions

REFER to: Handles, Locks, Latches and Entry Systems - System Operation and Component Description .

Possible Causes

- Fuse
- Wiring, terminals or connectors
- Door latch
- BCM

Visual Inspection and Diagnostic Pre-checks

- Check the BCM fuse 24 (30A)

DIAGNOSIS AND TESTING > LOCKS, LATCHES AND ENTRY SYSTEMS > PINPOINT TESTS > PINPOINT TEST J : A SINGLE OR MORE THAN ONE DOOR LOCK IS INOPERATIVE > PINPOINT TEST J : A SINGLE OR MORE THAN ONE DOOR LOCK IS