

Service Manual: FRONT DRIVE AXLE/DIFFERENTIAL

SPECIFICATIONS > SPECIFICATIONS > MATERIALS

Name	Specification
Premium Long-Life Grease XG-1-E1	ESA-M1C75-B
Threadlock 262 TA-26	WSK-M2G351-A6
Motorcraft® SAE 75W-85 Premium Synthetic Hypoid Gear Lubricant XY-75W85-QL	WSS-M2C942-A
Silicone Gasket and Sealant TA-30	WSE-M4G323-A4

SPECIFICATIONS > SPECIFICATIONS > CAPACITIES

Item	Liters
Material : Motorcraft® SAE 75W-85 Premium Synthetic Hypoid Gear Lubricant / XY-75W85-QL (WSS-M2C942-A)	1.66L (3.5 pt)
Material : Premium Long-Life Grease / XG-1-E1 (ESA-M1C75-B)	-
Material : Silicone Gasket and Sealant / TA-30 (WSE-M4G323-A4)	-
Material : Threadlock 262 / TA-26 (WSK-M2G351-A6)	-

SPECIFICATIONS > SPECIFICATIONS > GENERAL SPECIFICATIONS

Item	Specification
Backlash Specifications	
Ring gear backlash	0.204-0.305 mm (0.008-0.012 in)
Ring gear maximum backlash between teeth	0.101mm (0.004 in)
Clearance Specifications	