

SPECIFICATIONS > SPECIFICATIONS > MATERIALS

Name	Specification
Premium Long-Life Grease XG-1-E1	ESA-M1C75-B
Motorcraft ® SAE 75W-85 Premium Synthetic Hypoid Gear Lubricant XY-75W85-QL	WSS-M2C942-A
Silicone Gasket and Sealant TA-30	WSE-M4G323-A4

SPECIFICATIONS > SPECIFICATIONS > CAPACITIES

Item	Liters
Material : Motorcraft ® SAE 75W-85 Premium Synthetic Hypoid Gear Lubricant / XY-75W85-QL (WSS-M2C942-A)	1.93L (4.0 pt) (to the bottom of the filler hole)
Material : Premium Long-Life Grease / XG-1-E1 (ESA-M1C75-B)	-
Material : Silicone Gasket and Sealant / TA-30 (WSE-M4G323-A4)	-

SPECIFICATIONS > SPECIFICATIONS > GENERAL SPECIFICATIONS

Item	Specification
Available drive pinion bearing adjustment shim in steps of 0.025 mm (0.001 in)	0.381-1.219 mm (0.010-0.038 in)
Maximum axle shaft flange runout	0.076 mm (0.003 in)
Maximum differential case ring gear flange runout	0.076 mm (0.003 in)
Maximum pinion flange runout	0.279 mm (0.011 in)
Pinion bearing rotational preload	1.8-3.3 Nm (16-29 lb-in)
Ring gear backlash	0.203-0.304 mm (0.008-0.012 in)