

Specifications

General Specifications

2.7L EcoBoost Trim level XLT and lower	
Item	Specification
Voltage	12 Volts
Cold Cranking Amps (CCA) measured at -18 C (-0.4 F)	760 Cold Cranking Amps (CCA)
Battery amps rating	70 Ah
Battery size	H6
Battery type	Absorbed Glass Mat (AGM)

2.7L EcoBoost Trim level higher than XLT	
Item	Specification
Voltage	12 Volts
Cold Cranking Amps (CCA) measured at -18 C (-0.4 F)	800 Cold Cranking Amps (CCA)
Battery amps rating	80 Ah
Battery size	H7
Battery type	Absorbed Glass Mat (AGM)

3.0L Power Stroke Diesel

Item	Specification
Voltage	12 Volts
Cold Cranking Amps (CCA) measured at -18 C (-0.4 F)	850 Cold Cranking Amps (CCA)
Battery amps rating	92 Ah
Battery size	H8
Battery type	Absorbed Glass Mat (AGM)

3.3L Duratec, 3.5L EcoBoost and 5.0L Ti-VCT Trim level XLT and lower

Item	Specification
Voltage	12 Volts
Cold Cranking Amps (CCA) measured at -18 C (-0.4 F)	610 Cold Cranking Amps (CCA)
Battery amps rating	70 Ah
Battery size	H6
Battery type	Absorbed Glass Mat (AGM)

3.3L Duratec, 3.5L EcoBoost and 5.0L Ti-VCT Trim level higher than XLT

Item	Specification
Voltage	12 Volts
Cold Cranking Amps (CCA) measured at -18 C (-0.4 F)	730 Cold Cranking Amps (CCA)
Battery amps rating	80 Ah
Battery size	H7
Battery type	Absorbed Glass Mat (AGM)