

Specifications

Lubricants, Fluids, Sealers and Adhesives

Item	Specifications
Motorcraft® MERCON® LV Automatic Transmission Fluid (U.S.) XT-10-QLVC (U.S.)	MERCON® LV WSS-M2C938-A
Motorcraft® Multi-Purpose Grease XL-5-A	ESB-M1C93-B

General Specifications

Item	Specification
Steering Gear F250/350	
Meshload	0.31-0.9 Nm (2.65-7.96 lb-in)
Meshload + preload (maximum)	2.32 Nm (20.5 lb-in)
Steering gear preload	0.34-1.36 Nm (3-12 lb-in)
Turns lock-to-lock	4.0
Power Steering Pump	
Flow	10.6-12.0 L/min (2.8-3.2 gpm) Fluid @ 74-80°C (165-175°F) Engine at idle
Minimum Capacity	5.7 L/min (1.5 gpm) Fluid @ 80°C (175°F) Engine at idle Pressure 5,000 kPa (725 psi)
Power steering purge vacuum	68-85 kPa (20-25 in/Hg)
Pressure	1,034 kPa (150 psi) Fluid @ 74-80°C (165-175°F) Engine at idle
Relief pressure	12,100-12,900 kPa (1,755-1,871 psi)