

Specifications

Materials

Name	Specification
Motorcraft® Premium Cooling System Flush VC-1	ESR-M14P7-A
Motorcraft® Yellow Concentrated Antifreeze/Coolant VC-13-G	WSS-M97B57-A1
Motorcraft® Yellow Prediluted Antifreeze/Coolant VC-13DL-G	WSS-M97B57-A2

Materials

Antifreeze/Coolant	Fill Capacity
Material: Motorcraft® Yellow Concentrated Antifreeze/Coolant / VC-13-G (WSS-M97B57-A1)	31.7 qt (30.0L)
Material: Motorcraft® Yellow Prediluted Antifreeze/Coolant / VC-13DL-G (WSS-M97B57-A2)	31.7 qt (30.0L)
Material: Motorcraft® Premium Cooling System Flush / VC-1 (ESR-M14P7-A)	â€”

General Specifications

Item	Specification
Complete cooling system maximum pressure	Use individual readings listed on the pressure relief cap
Pressure relief cap	Use individual readings listed on the pressure relief cap
Radiator (out of vehicle)	138 kPa (20 psi)

Thermostat Opening Temperatures

Item	Specification
Starts to open â€” (low temperature)	88-92Â°C (190-198Â°F)
Fully open â€” (low temperature)	100Â°C (212Â°F)
Starts to open â€” (high temperature)	92-95Â°C (198-203Â°F)
Fully open â€” (high temperature)	103Â°C (217Â°F)