

SPECIFICATIONS > SPECIFICATIONS

Materials

Name	Specification
Motorcraft® Orange Prediluted Antifreeze/Coolant (U.S.) VC-3DIL-B (U.S.)	WSS-M97B44-D2
Motorcraft® Orange Concentrated Antifreeze/Coolant (U.S.) VC-3-B (U.S.)	WSS-M97B44-D

Materials

Material: Motorcraft® Orange Concentrated Antifreeze/Coolant (U.S.) / VC-3-B (U.S.) (WSS-M97B44-D)
Material: Motorcraft® Orange Prediluted Antifreeze/Coolant (U.S.) / VC-3DIL-B (U.S.) (WSS-M97B44-D2)

Cooling System Capacities

Description	Specification
Base engine with oil cooler	9.47 qt (8.96 L)

Cooling System Pressure

Complete cooling system maximum pressure	145 kPa (21 psi)
Pressure relief cap	145 kPa (21 psi)
Radiator pressure test (removed from the vehicle)	138 kPa (20 psi)

Thermostat Opening Temperatures

Starts to open	80°C-84°C (176°F-183.2°F)
Fully open	97°C (206.6°F)

DESCRIPTION AND OPERATION > ENGINE COOLING - COMPONENT LOCATION



NOTE: Coolant temperature will vary with ambient temperature and load. Temperatures