

Description and Operation

WARNINGS:



Cured polyurethane (PU) adhesive can degrade if subjected to high temperatures. Isocyanide compounds can be released when grinding or welding in close proximity to cured PU adhesive.



SKIN CONTACT: Prolonged exposure to polyurethane (PU) adhesive may cause skin irritation. If PU adhesive comes into contact with the skin, remove any contaminated clothing. Immediately wash the skin with soap and water. Seek medical attention for any persistent skin irritation or abnormality.



EYE CONTACT: Polyurethane (PU) adhesive may cause severe irritation or damage. If PU adhesive comes into contact with the eyes, immediately flush eyes with plenty of running water for at least 15 minutes. Seek immediate medical attention.



SWALLOWED: If polyurethane (PU) adhesive is swallowed, flush the mouth thoroughly. Do not induce vomiting. Provide rest, warmth and fresh air. Seek immediate medical attention.



INHALED: Persons having a respiratory allergy may have an allergic reaction when handling polyurethane (PU) adhesive.



INHALED: Polyurethane (PU) adhesive can cause asthma like symptoms. Isocyanate vapor from primer or PU adhesive can cause allergies in the respiratory tract.



INHALED: If polyurethane (PU) adhesive fumes are inhaled, move victim to fresh air. Provide oxygen if necessary. If breathing stops, provide artificial respiration. Keep a victim warm and at rest. Seek immediate medical attention.

NOTICE:



Make sure that the direct glazing for bonded glass cutting blades are changed where the cutting depth changes to avoid damage to the body and trim panels.



During the curing period of the PU adhesive, the door windows must be left open to avoid a build up of pressure when the doors are opened and closed.