

Suspension System - General Information - Specifications

 Print

FRONT WHEEL ALIGNMENT (DECIMAL DEGREES AT CURB)

BODY	WHEELBASE	GVM	CAMBER	CASTER	TOTAL TOE	SIDE TO SIDE CASTER	CLEARVISION
Van	SWB	≤3100	-0.57	2.16	0.27	0	0
		3100<	-0.58	1.7	0.27	0	0
	MWB	≤3100	-0.5	2.35	0.27	0	0
		3100<	-0.48	1.95	0.27	0	0
Kombi/DCIV	SWB	≤3100	-0.67	2.07	0.27	0	0
		3100<	-0.69	1.76	0.27	0	0
	MWB	≤3100	-0.63	2.2	0.27	0	0
		3100<	-0.67	1.97	0.27	0	0
Bus	SWB	-	-0.73	2.25	0.27	0	0
	MWB	-	-0.65	2.42	0.27	0	0
Sport Van	SWB	-	-0.27	2.07	0.27	0	0
Tolerance			±0.5	±0.6	±0.25	±0.7	±3.0

- ***GVM: Gross Vehicle Mass**
- **DCIV: Double Cab in Van**

REAR WHEEL ALIGNMENT (DECIMAL DEGREES AT CURB)

CAMBER	TOE PER SIDE	THRUST
-1°±0.5°	0.2°±0.4°	0°±0.45°