

LUBRICANTS, FLUIDS, SEALERS AND ADHESIVES

VAN	SPECIFICATION
Refrigerant R134a	WSH-M17B19-A
Refrigerant oil	WSH-M1C231-B

LUBRICANTS, FLUIDS, SEALERS AND ADHESIVES

BUS	SPECIFICATION
Refrigerant R1234yf	WSS-M17B21-A
Refrigerant oil	WSS-M2C300-A2

REFRIGERANT CAPACITIES (TOTAL REQUIRED REFRIGERANT CHARGE)

VAN	GRAMS
Air Conditioning	740 ± 15
A/C system with Auxiliary A/C system	1150 ± 15

REFRIGERANT CAPACITIES (TOTAL REQUIRED REFRIGERANT CHARGE)

BUS	GRAMS
Air Conditioning	740 ± 15
A/C system with Auxiliary A/C system	1050 ± 15

REFRIGERANT OIL CAPACITIES (TOTAL REQUIRED REFRIGERANT OIL CHARGE)

	MILLILITRES
Air Conditioning	160
A/C system with Auxiliary A/C system	245

ADDITION OF REFRIGERANT OIL (WHEN NEW COMPONENTS ARE INSTALLED)**NOTICE: The refrigerant oil top-up quantity must not exceed the refrigerant oil fill quantity.**

	MILLILITRES
After renewal of all lines and components, or if system gets flushed	add the total required oil charge (new compressor as delivered ie. 160 or 245).