

ADDITIONAL OPERATIONS TO BE CARRIED OUT DURING SERVICING

Servicing periods are the same for LPG-equipped cars as those for equivalent models with petrol engines.

Also:

All services must include:

- a check on the safety solenoid valve,
- a check for the presence of a blanking cover on the pressure relief valve.

All services must include:

- a gas filter change.

Every eight years:

- a hydraulic test must be performed on the LPG tank.

Vehicles	Replace spark plugs	Check/adjust the valve clearances
KANGOO - CLIO II - TWINGO - ESPACE	every 18 000 miles (30 000 km)	every 18 000 miles (30 000 km) except for 16V engines

CHECKING THE OIL LEVEL

Renault engines are designed and built to the highest technological standards, and naturally need a little oil for optimum running.

For this reason, and to avoid any potential engine failure, the engine oil level must be **regularly checked** in particular before long journeys.

It may be necessary to top up the oil once or twice between changes and especially during the running in period; **do this when the oil is level with the minimum mark on the gauge.**

The level should be checked with the car on a flat surface, with the engine stopped and cold (e.g.: before the engine is started for the first time of the day).

Let the oil settle after refilling (approximately **2 minutes**), (**15 minutes** for Master vehicles) before checking the level with the dipstick.

It is very important not to exceed the maximum mark on the gauge (in this case oil consumption is greater; it can also cause engine damage).

mcx30.com