

119	Torque tighten the front wheel on the passenger's side and refit the trim (if equipped)	Refitting the trim confirms the tightening operation.
Administrative operations		
120	Fill in the test certificate	
121	Indicate, according to the degree of importance, the next works to be performed in order to ensure vehicle conformity.	
Final inspection in the engine compartment:		
122	Fill in and position the maintenance label	
123	After waiting at least 10 minutes after the last top-up or starting the engine, check the oil level using the dipstick	
124	Top up if necessary	
125	Clean the engine cover and the battery cover	



Repair-00x01x01x28-02x32-1-1-1.xml



MAINTENANCE VALUES: DESCRIPTION

Special tooling required

Brake calliper piston return tool.	Fre. 1190-01
14 mm Plug spanner.	Ele. 1382-01
8 mm square engine drain plug spanner.	Mot. 1018
Torque wrench for spark plugs	Ele. 1933

1. ENGINE MAINTENANCE SUMMARY

Note:

(*) The engine oil grade and viscosity only applies to the following countries:



Germany, Andorra, Austria, Belgium, Denmark, Spain, Estonia, Finland, France, Great Britain, Greece, Hungary, Ireland, Iceland, Italy, Latvia, Liechtenstein, Lithuania, Luxembourg, Norway, Netherlands, Poland, Portugal, Czech Republic, Slovakia, Slovenia, Sweden, Switzerland, Croatia, Israel.

Important: for vehicles in countries which are not listed above, please refer to Technical Note 6013A [Engine oil: Specifications](#) .

	Engine oil grade (*)	RN0720
OIL	Oil viscosity (*) depending on external temperature	t > -20°C 5W30 or 5W40 t > -25°C 5W30 or 5W40 t > -30°C 0W30 or 0W40
	Engine oil capacity with oil filter replacement	4.7 litres

DRAIN PLUG	Tool	8 mm square engine drain plug spanner.(Mot. 1018)
	Tightening torque	50 N.m
OIL FILTER	Tool	27 mm spanner
	Other tightening	25 N.m

PLUG	Tool	14 mm Plug spanner.(Ele. 1382-01) Torque wrench for spark plugs(Ele. 1933)
	Tightening torque	24 N.m
	Electrode gap	0.7 + 0 / - 0.1 mm Not adjustable
COIL	Tightening torque	10 N.m

2. CHASSIS MAINTENANCE SUMMARY

WHEELS	Tightening torque	105 N.m
--------	-------------------	---------

BRAKE FLUID	Brake fluid grade	DOT 4, ISO CLASS 6, RENAULT Standard: 03-50-006
-------------	-------------------	---

FRONT BRAKES