

Tools	Tool	Brake calliper piston return tool.(Fre. 1190-01)
Tightening torques	Front disc bolts	20 N.m
	Front guide pin bolts	27 N.m
	Front calliper support bolts	105 N.m
Measurement	Front disc diameter	258 mm
	Minimum front brake disc thickness	19.8 mm
	Minimum front brake pad thickness	10 mm

REAR BRAKES

Tightening torque	Rear drum nut	175 N.m
Measurement	Rear drum diameter	203.2 mm
	Maximum rear drum diameter	204.4 mm
	Minimum rear lining thickness	2.4 mm



Repair-00x01x01x27-02x21-2-101-1.xml



XSL version : 3.02 du 22/07/11

MANUAL GEARBOX OIL: SPECIFICATIONS



Note, one or more warnings are present in this procedure



WARNING

Before carrying out any operation on a vehicle fitted with the Stop & Start system, always follow the safety instructions [Vehicle: Precautions for the repair](#) .

1. GEARBOX TYPE/OIL TYPE CORRELATIONS:

mcx30.com

GEARBOX TYPE	TYPE OF OIL FOR GEARBOX
JBX	TRANSELF TRJ 75W80 or TRANSELF NFJ 75W80
JCX	
JEX	
JRX	
JHX	
JSX	
NDX	
TLX	
PKX	TRANSELF TRX 75W80 or TRANSELF NFP 75W80
PFX	
VMX	
NEX	
NGX	
N0X	
UNX	
ZFX	TRANSELF LD 75W80

Component identification:

The third character Xcorresponds to the figure written on the identification plate and therefore covers the entire manual gearbox range.

2. STANDARDS AND PART NUMBERS OF THE VARIOUS RECOMMENDED OILS:

DESIGNATION	STANDARD	PART NUMBER
TRANSELF TRX 75W80 or TRANSELF NFP 75W80	APIGL4, MIL-L-2105 C or D	7711573523 (5 litres)
TRANSELF TRJ 75W80 or TRANSELF NFJ 75W80	APIGL4, MIL-L-2105 C or D	7711226421 (1 litre)
TRANSELF LD 75W80	APIGL4, MIL-L-2105	May be ordered from ELF

3. IDENTIFICATION OF OIL FOR STANDARD EXCHANGE PK1 GEARBOXES:

Note:



For standard exchange PK1 gearboxes, the oil type (TRZ or TRP) is shown on a label.

These two oils are replaced by TRX 75W80 or NFP 75W80.

