



mcx30.com

NEWVEHICLEMAINTENANCE:DESCRIPTION



Note, one or more warnings are present in this procedure



WARNING

Before carrying out any operation on a vehicle fitted with the Stop & Start system, always follow the safety instructions [Vehicle: Precautions for the repair](#)

This Technical Note describes the steps to be followed for the maintenance of new vehicles during storage. You can use this Technical Note as a monitoring sheet: Enter into the appropriate box the date that the operation is carried out.

This sheet should be stored in the storage compartment of the driver's side front door until the vehicle is prepared before delivery.

1.

VIN:	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Factory release date:	-- / -- / ----																

MAINTENANCE OPERATIONS

	At 3 months	At 6 months	At 9 months	> = 12 months
Recharge the battery (see Battery - Charge) (Technical Note 6512A, 80A, Battery)	X	X	X	
After each recharge, disconnect the battery Battery: Removal - Refitting (See MR for the vehicle), for Mégane II, Scénic II, Espace IV, Koleos.	X	X	X	
Replace the battery whilst the vehicle is being prepared before delivery Battery: Removal - Refitting				X
Remove the foam panels Removing the vehicle protection: Description	X			
Remove the protection film or copolymer layer Removing the vehicle protection: Description		X		

Additional operations for a vehicle stored in the showroom