

A-PILLAR REPLACEMENT



Note, one or more warnings are present in this procedure



WARNING

DANGER: HIGH VOLTAGE VEHICLE.




Risks of serious burns or electric shocks that may prove fatal.

Before carrying out any work on the vehicle, it is essential that you follow the instructions regarding vehicle lockout. This work must be carried out by an employee who is qualified and authorised to work on a high-voltage onboard network [Vehicle:](#)

[Precautions for the repair](#) .

Lockout the vehicle [Vehicle: Lockout - Removal of lockout](#) .

1. COMPOSITION OF THE SPARE PART




No.	Description	Thickness (mm)
(1)	A-pillar	0.7
(2)	A-pillar blanking cover	0.65

2. IN THE EVENT OF REPLACEMENT

■ The options for replacing this part are as follows:

- complete replacement A-C,
- partial replacement B-C.



CAUTION

If the mating faces of the parts to be welded are not accessible, make EGW plug welds to replace the original resistance welds (see MR 400).

CAUTION



To avoid damaging the vehicles electric and electronic components, the earths of any wiring harness near the weld area must be disconnected.


Position the earth of the welding machine as close as possible to the weld area (see MR 400).

Locate the earths located near to the weld area [Earths on body: List and location of components](#) .

1- COMPLETE REPLACEMENT


1)PART IN POSITION

mcx30.com




156772

DETAILED VIEW A



DETAILED VIEW C




156773

2)IRREMOVABLE BODYWORK COMPONENTS - STRUCTURES TO BE REMOVED IN ORDER TO CARRY OUT THE REPLACEMENT OPERATION


Remove the roof [Roof: Replacement](#) .

2- PARTIAL REPLACEMENT B-C


1)PART IN POSITION



DETAILED VIEW B



DETAILED VIEW C



156773



Repair-40x08x02-02x49-1-4-1.xml

